



NEWTEX



Fluorosynthetic Foam AFFF - AR

PHYSICAL DATA

	NEWTEX		
	30	30RS	30RS-30
Appearance / Colour	Yellow liquid		Green liquid
Concentration of use	10%	100%	
Specific Gravity at 20°C (Kg/dm3)	1.02	1.00	1.05
Viscosity at 20°C (cStokes)	5	3	60
Freezing point	-10°C	-3°C	-32°C
Ph at 20°C	7		
Sediment after ageing	<0.1%		
Surface tension (mN/m)	16	16	17
Interfacial tension (mN/m)	2	2	3

PERFORMANCE & WARRANTY

NEWTEX meets international requirements
EN 1568-3: Class IB
ISO 7203-1
EN3

NEWTEX does not contain any gum.

NEWTEX is designed to work effectively in extinguishers.
It is formulated to enable AR rating on solvents.

EXTINGUISHER - Typical ratings:

6 Litre	13A	113B	34B-AR
9 Litre	21A	183B	34B-AR

NEWTEX has a 5 years warranty in its original packaging and at storage temperatures -30°C/+60°C.

NEWTEX has a 5 years warranty as a premix solution, contained and sealed in a lined extinguisher unit or fire suppression system.

FOAM QUALITY

Low Expansion	8
Drainage time 25% / 50%	3min. / 5 min.



Tel. +44 (0) 1536 202919 • Fax +44 (0) 1536 263641 • sales@3fff.co.uk

Unit B, 18 Brunel Road, Earlstree Industrial Estate,
Corby, Northants, NN17 4JW, United Kingdom

V.A.T. Registration No: 938 9418 70 • Registered in England: 06236589

No: FM 560021

www.3fff.co.uk